

# **FILTERSIL**

# Safety Data Sheet

Supersedes: January 7, 2021 Revised: May 13, 2021

#### SECTION I - PRODUCT AND SUPPLIER INFORMATION

Supplier: Prairie Mud Service

738 6th Street, Estevan, SK S4A 1A4

306-634-3411

**Emergency Response Telephone:** CANUTEC - (613) 996-6666 or \*666 on cellular phone)

**PRODUCT** 

California Tan Nursery Grit **Target Engine Sand** 

**Target Filter Sand and Gravel Target Premium Filter Sand and Gravel** 

**Target Geothermal Sand Target Silica Engine Sand** Target Slurry Filler

**Target Winter White Forestry Sand** 

**Target Epoxy Gravel** 

**PRODUCT USE** 

**Nursery Grit Locomotive Traction Sand** Filter Medium/ Inorganic Filler Filter Medium/ Inorganic Filler **Geothermal Grout Applications Locomotive Traction Sand** 

Mortar and Coating Filler

**Nursery Grit** 

Filler

Product Use: Silica sands for various construction practices

For the most recent version of this document, visit www.targetproducts.com

# **SECTION II - HAZARD IDENTIFICATION**

# Hazard-determining components of labeling: Silica 2.1 Classification of the substance or mixture

Carcinogen - Category 1A Specific Target Organ Toxicity Single Exposure - Category 3 Specific Target Organ Toxicity Repeat Exposure - Category 1 Eye Irritant - Category 2B

# 2.2a Signal word DANGER!

# 2.2b Hazard Statements

May cause cancer through chronic inhalation May cause respiratory irritation Causes damage to lungs through prolonged or repeated inhalation Causes eye irritation if particles or dust get in eye

Industrial hygiene experts have studied long-term daily use of silica sands in sand-blasting and other occupations generating extreme volumes of dust. They have determined that long term, daily exposure to high concentrations of blasting sand dust causes damage to the lungs, may cause silicosis, and may cause cancer. Do not use for sand blasting. There are extensive OSHA precautions required for sand blasting.

# 2.2c Pictograms



# 2.2d Precautionary statements

Do not handle until all safety precautions have been read and understood.

Wear protective gloves, eye protection, and protective clothing.

Do not eat, drink or smoke when using this product.

Wash thoroughly after handling.

Use only in a well-ventilated area.

Do not breathe dust.

If inhaled: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and

easy to do. Continue rinsing.

#### Immediately seek medical advice or attention if symptoms are significant or persist.

Dispose of contents/containers in accordance with all regulations.

#### 2.3 Additional Information

2.3a HNOC - Hazards not otherwise classified: Not applicable

2.3b Unknown Acute Toxicity: None

SECTION III - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION				
Hazardous Components	CAS No.	% by Weight		
Sand, Silica, Quartz	14808-60-7	60-100		

# **SECTION IV - FIRST AID MEASURES**

# 4.1 Description of the first-aid measures

General information:

After inhalation: Remove person to fresh air and keep comfortable for breathing.

After skin contact: Rinse skin with water.

After eye contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

insing.

**After swallowing:** If conscious, have the victim drink plenty of water and call a physician immediately. Never give anything by mouth to an unconscious person.

# 4.2 Most important symptoms/effects, acute and delayed

**Inhalation:** May cause respiratory tract irritation. Causes damage to organs through prolonged or repeated inhalation. This product contains crystalline silica. Prolonged or repeated inhalation of respirable silica from this product can cause silicosis.

Skin contact: Causes mechanical skin irritation.

Eve Contact: Causes eye irritation if particles or dust get in eye.

Ingestion: Ingestion of large quantities may cause discomfort and/or distress, nausea or vomiting.

# 4.3 Indication of immediate medical attention and special treatment needed:

Immediately seek medical advice or attention if symptoms are significant or persist.

# **SECTION V - FIRE FIGHTING MEASURES**

**5.1 Flammability of the Product:** Non-flammable and non-combustible

**5.2 Suitable extinguishing agents:** Treat for surrounding material

5.3 Special hazards arising from the substance or mixture: None

5.3a Products of Combustion: None

5.3b Explosion Hazards in Presence of Various Substances: Non-explosive in presence of shocks

# SECTION VI - ACCIDENTAL RELEASE MEASURES

**6.1 Personal precautions, protective equipment and emergency procedures:** Wear personal protective equipment (See section VIII). Keep unprotected persons away.

# 6.2 Methods and material for containment and cleaning up:

Do not allow to enter sewers/ surface or ground water. Dispose of unwanted materials and containers properly in accordance with all regulations.

#### SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND STORAGE

#### 7.1 Handling

Precautions for safe handling: Do not use for sand blasting. There are extensive OSHA precautions required for sand blasting. Ensure good ventilation/exhaustion at the workplace. DO NOT BREATHE DUST. In dusty environments, the use of an OSHA, MSHA or NIOSH approved respirator and tight fitting goggles is recommended. Wear appropriate PPE (See section 8).Do not mix with other chemical products, except as indicated by the manufacturer. Do not get in eyes, on skin or clothing. Good housekeeping is important to prevent accumulation of dust.

#### 7.2 Storage

Requirements to be met by storerooms and receptacles: No special requirements.

Information about storage in one common storage facility: Not required.

Further information about storage conditions: Keep out of the reach of children.

# SECTION VIII - EXPOSURE CONTROL MEASURES / PERSONAL PROTECTION

8.1 Components with limit values that require monitoring at the workplace:

Hazardous Components CAS No. PEL (OSHA) TLV (ACGIH)

 $mg/M^3$   $mg/M^3$ 

Silica Sand, crystalline 14808-60-7 0.05 0.025 (resp)

#### 8.2 Exposure Controls

Use ventilation adequate to keep exposures below recommended exposure limits.

# 8.3 General protective and hygienic measures

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin.

#### 8.3a Personal protective equipment

#### Protection of hands:

Wear gloves of adequate length to offer appropriate skin protection from incidental contact. General duty work gloves have been found to offer adequate protection for most intended uses.

#### Eve protection:

Wear approved eye protection properly fitted dust- proof chemical safety glasses.

## Respiratory protection:

A NIOSH-approved dust mask or filtering face piece is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirators should be selected by and used under the direction of a trained health and safety professional, following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2).

## SECTION IX - PHYSICAL/CHEMICAL CHARACTERISTICS

**General Information** 

Appearance Form: Granular Solid

Color: Varies Odor: None

pH-value at 20°C (68 °F):

Boiling point/Boiling range:

Flash point:

Not applicable

Not applicable

**Auto igniting:** Product is not self-igniting

Vapor pressure at 21°C (70°F) Not applicable

**Density at 25°C (77 °F):** 2.5-2.8

Solubility in / Miscibility with

Water: Insoluble VOC content: 0 g/L VOC

# SECTION X - STABILITY AND REACTIVITY

# 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

# 10.2 Chemical stability

Stable under normal storage conditions. Keep in dry storage.

#### 10.3 Possibility of hazardous reaction

No dangerous reaction known under conditions of normal use.

#### 10.4 Thermal decomposition / conditions to be avoided

No decomposition if used according to specifications.

# 10.5 Incompatible materials

Contact of silica with powerful oxidizing agents such as fluorine, chlorine trifluoride, manganese trioxide, or oxygen difluoride may cause fires

# 10.6 Hazardous Decomposition or By-products

Silica will dissolve in Hydrofluoric Acid and produce a corrosive gas – silicon tetrafluoride.

# **SECTION XI - TOXICOLOGICAL INFORMATION**

11.1 Exposure Routes: Inhalation, skin contact, eye contact, or ingestion.

#### 11.2 Symptoms related to physical/chemical/toxicological characteristics:

**Inhalation:** May cause respiratory tract irritation. Causes damage to organs through prolonged or repeated exposure. This product contains crystalline silica. Prolonged or repeated inhalation of respirable silica from this product can cause silicosis.

Skin contact: May cause mechanical skin irritation.

Eye Contact: Causes eye irritation if particles or dust gets in eye.

Ingestion: Ingestion of large quantities may cause discomfort and/or distress.

# 11.3 Delayed, immediate and chronic effects of short-term and long-term exposure Short Term

Skin Corrosion/Irritation: Not applicable

Serious Eye Damage/Irritation: Causes eye irritation if particles or dust gets in eye

Respiratory Sensitization: Not applicable

Skin Sensitization: Not applicable

Specific Target Organ Toxicity-Single Exposure: (Category 3) May cause respiratory irritation

Aspiration Hazard: Not applicable

# Long Term

Carcinogenicity: May cause cancer through chronic inhalation.

Germ Cell Mutagenicity: Not applicable Reproductive Toxicity: Not applicable

Specific Target Organ Toxicity- Repeated Exposure: (Category 1) Causes damage to lungs through prolonged/repeated

exposure

Synergistic/Antagonistic Effects: Not applicable

## **SECTION XII - ECOLOGICAL INFORMATION**

# 12.1 Ecotoxicity

No further relevant information available.

# 12.2 Persistence and degradability

No further relevant information available.

## 12.3 Bioaccumulative potential:

No further relevant information available.

#### 12.4 Mobility in soil

No further relevant information available.

#### 12.5 Other Adverse Effects

No further relevant information available.

# SECTION XIII - DISPOSAL CONSIDERATIONS

# 13.1 Waste Disposal Method

The packaging and material may be land filled; however, material should be covered to minimize generation of airborne dust. This product is <u>not</u> classified as a hazardous waste under the authority of the RCRA (40CFR 261) or CERCLA (40CFR 117&302). Disposal must be made in accordance with local, state and federal regulations.

#### 13.2 Other disposal considerations

Uncleaned packaging

**Recommendation:** Disposal must be made in accordance with local, state and federal regulations.

Recommended cleansing agent: Water, if necessary with cleansing agents.

SECTION XIV – TRANSPORT INFORMATION			
	DOT (U.S.)	TDG (Canada)	
UN-Number	Not Regulated	Not Regulated	
UN proper shipping name	Not Regulated	Not Regulated	
Transport Hazard Class(es)	Not Regulated	Not Regulated	
Packing Group (if applicable)	Not Regulated	Not Regulated	

#### 14.1 Environmental hazards:

Not applicable

#### 14.2 Transport in bulk according to Annex II of Marpol 73/78 and the IBC Code

Not applicable

# 14.3 Special precautions for user

Do not handle until all safety precautions have been read and understood.

# SECTION XV - OTHER REGULATORY INFORMATION

# 15.1 Safety, Health and Environmental Regulations/Legislations specific for the chemical

# 15.2 US Federal Information

# SARA 302/311/312/313 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302, 311, 312 or 313. **RCRA:** Crystalline silica (quartz) is not classified as a hazardous waste under the Resource Conservation and Recovery Act, or its regulations, 40 CFR §261 et seq.

**CERCLA:** Crystalline silica (quartz) is not classified as a hazardous substance under regulations of the Comprehensive Environmental Response Compensation and Liability Act (CERCLA), 40 CFR §302.

Emergency Planning and Community Right to Know Act (SARA Title III): Crystalline silica (quartz) is not an extremely hazardous substance under Section 302 and is not a toxic chemical subject to the requirements of Section 313.

**FDA:** Silica is included in the list of substances that may be included in coatings used in food contact surfaces, 21 CFR §175.300(b)(3)(xxvi).

**NTP:** Respirable crystalline silica, primarily quartz dusts occurring in industrial and occupational settings, is classified as Known to be a Human Carcinogen.

OSHA Carcinogen: Crystalline silica (quartz) is not listed.

# 15.3 State Right to Know Laws

#### California Prop. 65 Components

**WARNING:** This product can expose you to crystalline silica which is known to the State of California to cause cancer. For more information go to <a href="https://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>.

California Inhalation Reference Exposure Level (REL): California established a chronic REL of 3 µg for silica (crystalline, respirable). A chronic REL is an airborne level of a substance at or below which no adverse health effects are anticipated in individuals indefinitely exposed to the substance at that level.

Massachusetts Toxic Use Reduction Act: Silica, crystalline (respirable size, <10 microns) is "toxic" for purposes of the Massachusetts Toxic Use Reduction Act.

#### 15.4 Global Inventories

**DSL** All components of this product are on the Canadian DSL list.

**TSCA No.:** Crystalline silica (quartz) appears on the EPA TSCA inventory under the CAS No. 14808-60-7. All constituents are listed in the TSCA inventory.

# SECTION XVI - OTHER INFORMATION

Last Updated: May 13, 2021

**NOTE:** The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to silica contained in our products.